

SANDING RECOMMENDATION PALLMANN SPIDER FLEX DISC

Requirement / Abrasive Abrasive color	Coarse	Standard			Fine
	CERAMIC PLUS 178 MM 	CERAMIC PLUS 178 MM 	ZIRCONIA 178 MM 	SILICIUM CARBID 178 MM 	SILICIUM CARBID 178 MM 
PALLMANN Item-No.	83655	83903	62003	83905	83906
Raw wood	for uneven floors				
Oiled wood floor surface					recommended
Sealed wood floor surface	for stubborn seal				
Remarks / Recommendation					
Flex disc (169518)					
Support Pad soft (75684)					
Power reserve	yes	yes	yes	optional	optional
Additional weight	1	1	1	1	1
Rotation speed	75 %	50 – 75 %	50 %	25 – 50 %	25 – 50 %

If you have any questions please contact your PALLMANN technical manager.

SANDING RECOMMENDATION PALLMAN SPIDER PADS SYSTEM

Requirement / Abrasive Abrasive color	Coarse	Standard			Fine
	CERAMIC PLUS 178 MM 	CERAMIC PLUS 178 MM 	ZIRCONIA 178 MM 	SILICIUM CARBID 178 MM 	SILICIUM CARBID 178 MM 
PALLMANN Item-No.	83655	83903	62003	83905	83906
Raw wood	for uneven floors				
Oiled wood floor surface					recommended
Sealed wood floor surface	for stubborn seal				
Remarks / Recommendation					
Exhaust pad (75685)					
					
Support Pad soft (75683)					
Power reserve	yes	yes	yes	optional	optional
Additional weight	1	1	1	1	1
Rotation speed	75 %	50 – 75 %	50 %	25 – 50 %	25 – 50 %

If you have any questions please contact your PALLMANN technical manager.